ANTI-NOISE RUBBER MAT



INDEX

- 1. Code Registry
- 2. Use
- 3. Installation
- 4. Technical Specification
- 5. Storage

1. CODE REGISTRY

| Code | Description | Dimension (mm) | Weight | Pkg. / Pallet |
|------------|-----------------------|----------------------|----------|--------------------|
| TER09-1144 | Anti-noise rubber mat | 200 x 200 - thick. 3 | - kg/pcs | 80 pcs / 6.720 pcs |
| MATERIAL | Made of rubber (TPV). | | | |

MATERIAL

2. USE

Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 12 dB.

3. INSTALLATION

 \cdot Clean the surface to be insulated, removing any unevenness present.

• Spread the mat with the smooth surface facing upwards.

· Place a protective film in polyethylene or similar and proceed with the laying of the flooring laying screed.

4. TECHNICAL SPECIFICATION

| Specification | Description | Unity | Price |
|-------------------|---|-------|-------|
| Dak.D. TER09-1144 | Supply and installation of Sound absorbing rubber mat for Arkimede range telescopic support. Thickness 3 mm. Made of rubber (TPV). Used to be positioned at the base of the ARKIMEDE range telescopic support to reduce footfall noise up to 12 dB. | pcs | - |

5. STORAGE

Store away from direct sunlight.



This data sheet supersedes and replaces all previous ones. The information contained herein is accurate to our present knowledge. Dakota Group S.a.S. assumes no responsibility or liability with respect to the information given. Dakota Group S.a.S. reserves the right to change speci cations and models without prior notice. Dakota Group S.a.S. - Via Don Cesare Scala, 55 - Brentino Belluno (VR) - Italy - tel. 045-6284080 - fax. 045-6284075 www.dakota.eu - info@dakota.eu o u cio.tecnico@dakota.eu

